

ROTATING LASER

With a full range of functions including dual grade slope, horizontal/vertical operation scan mode and various run speeds, the 88R is the class leader for all professional levelling tasks, with a full metal light house sensor based self-levelling, dual battery pack and heavy duty reinforced hi-viz casing.

The 88R is the leader in the field...

88R **RED BEAM**





Tripods and Staffs extra options

Specification:

Self Levelling	± 5°
Accuracy	1.5mm @ 30m
Working Distance	Dia 500m with included detector
Rotation Speeds	0, 60, 120, 300, 600rpm
Scan Mode	0°, 10°, 45°, 90°, 180°
Grade Slope	± 5° Dual Grade (X or Y Axis) 8.8%
Plumb Spot	± 5° 1mm @ 1.5m
Light Source	Laser Diode, 635nm
Remote Control	Working Range 20m
Horizontal/Vertical	Yes
IP Rating	IP66
Battery	Ni-mh Rechargeable & Alkaline 20 hrs Ni=mh, 60 hrs Alkaline
Low Battery Light	Yes
Battery Charger	240v
Working Temperature	0°C-40°C
Detector	Fine and course setting, 45mm vertical range
Weight	2.2kgs
Kit	Laser, Detector with bracket, Remote, Charger, Hard carry case Alkaline battery.